

NOTES:

- 1. COMMERCIAL DRIVEWAYS TO HAVE 6 INCH X 6 INCH 10/10 WIRE MESH EXTENDED INTO GUTTER PAN.
- 2. DRIVEWAY LANDING, SIDEWALK, CURB & GUTTER TO BE MONOLITHIC POUR TO A.C. LINE.
- 3. CURB HEIGHT AT LANDING SHALL BE 1 INCH MINIMUM AND 2 INCH MAXIMUM (3 INCH MAX UPON CARSON CITY PUBLIC WORKS APPROVAL) 2 INCH RADIUS TO BE USED WHEN CURB HEIGHT AT LANDING IS GREATER THAN 2 INCHES.
- 4. DRIVEWAY APRONS SHALL BE CONSTRUCTED IN COMPLIANCE WITH STANDARD DETAILS C-5.1.1 AND C-5.2.1.

NO.	REVISI	ON	DATE	STANDARD	DETAIL F	OR PUBLIC	WORKS	CONSTRUCTION	SECTION	
									CARSON CITY	
				P.C.C	C. DI	RIVEW	'AY	APRON	DRAWING NO.	
							4	<i>,</i>	C-5.2.3	
APPROV	/ED BY: /	18.	7/09			TYPE	1		DATE 7/2009	
		<u> </u>	7,00						772003	