



UTILITY	TYPICAL DEPTH OF COVER	MIN DEPTH OF COVER	MIN HORIZ SEPARATION	MIN VERT SEPARATION	MIN HORIZ SEPARATION FROM <b>WATER</b>	MIN VERT SEPARATION FROM <b>WATER</b>
STORM DRAIN	2'	2'	2'	1.5'	10'	1.5'
SANITARY SEWER	6'	4'	3'	1.5'	10'	1.5'
WATER MAIN RECLAIMED WATER GAS MAIN *, **	4'	3.5'	5'	1.5'	N/A	N/A
	5'	5'	5'	1.5'	10'	1.5'
	3'	2.5'	6'	2'	6'	2'
C.A.T.V. *, **	3'	3'	PER UTILITY CO	PER UTILITY CO	5'	1.5'
ELECTRICITY *, **	5'	5'	PER UTILITY CO	PER UTILITY CO	5'	2'
TELEPHONE *, ** 3.5		3.5'	PER UTILITY CO	PER UTILITY CO	5'	1.5'

\* MINIMUM OR LOCAL UTILITY STANDARDS — WHICHEVER IS GREATER \*\* SEE NOTE 5

## NOTES: 1

- 1. FOR COMMON TRENCH SECTION, SEE DETAIL, DWG. C-1.2.1. COMMON TRENCH WITH OTHER UTILITIES IS NOT ALLOWED FOR WATER, SEWER, RECLAIMED WATER OR STORMWATER.
- 2. DEPTHS OF COVER AND LOCATION OTHER THAN THOSE PROVIDED HEREIN ARE SUBJECT TO CARSON CITY DEVELOPMENT ENGINEERING & PUBLIC WORKS APPROVAL.
- 3. LOCATION AND DEPTH SHALL BE AS REQUIRED TO MEET THE REQUIREMENTS OF NAC CHAPTER 445A AND THE NDEP BUREAU OF SAFE DRINKING WATER VERTICAL CROSSING CONFLICTS SUMMARY.
- 4. DEPTH SHALL BE AS REQUIRED TO PROVIDE ADEQUATE CLEARANCE FROM OTHER UTILITIES AND TO SERVE UPSTREAM TRIBUTARY AREAS, AND TO MEET PROPER DESIGN REQUIREMENTS FOR DOWNSTREAM CONNECTIONS.
- 5. HORIZONTAL AND VERTICAL SEPARATIONS MUST BE PROVIDED UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.

	NQ.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	SECTION
ľ	/1\	NOTES &			CARSON CITY
Ì		SEPARATIONS	3/22	TYPICAL UTILITY	DRAWING NO.
Ì				MAIN LOCATIONS	C-1.2.4 DATE
	APPRO	ved by: <u>R</u>	3/22	MAIN LOCATIONS	MAR 2022