

TYPICAL SECTION

NOTES:

- 1. SIGN MATERIALS, CONSTRUCTION AND PLACEMENT MUST BE IN CONFORMANCE WITH THE LATEST EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- 2. STREET NAME SIGN MUST BE AS SPECIFIED IN STANDARD DETAIL DRAWING NO. C-5.4.1
- 3. ON STREETS WHERE CURBING DOES NOT EXIST, SET SIGN 6 FEET MINIMUM FROM PAVEMENT EDGE.
- 4. CONCRETE BASE MUST BE LOCATED AT BACK OF SIDEWALK, UNLESS OTHERWISE DIRECTED BY THE CITY ENGINEER.
- 5. ALL REGULATORY SIGNS MUST USE ASTM TYPE 3 OR 4 INTENSITY SHEETING.
- 6. ALL WARNING SIGNS MUST HAVE BLACK LETTERING ON YELLOW BACKGROUND UNLESS REQUIRED AND APPROVED FOR USE IN SCHOOL ZONE AREAS.

	NQ.	REVISION	DATE	STANDARD DETAIL FOR PUBLIC WORKS CONSTRUCTION	SECTION
ſ	/ 1\	RENUMBER	3/22		CARSON CITY
İ			,	TRAFFIC SIGN	DRAWING NO.
				INSTALLATION	C-5.4.1.1 Z> DATE
	APPRO'	APPROVED BY: X 3/22		IIISTALLATION	MAR 2022